

Thermoid Welding Hose

HBD INDUSTRIES, INC.

- ★ **Lightweight and flexible**
- ★ **Kink resistant**
- ★ **Brighter, cleaner colours**
- ★ **Clean smooth tube**
- ★ **Made in U.S.A.**
- ★ **MVP cover, operating temperature -40°F to +212°F**



Twin Welding Hose - Smooth Cover

I.D.	O.D.	No. of Spirals	Working Pressure	Weight per 100'
3/16"	7/16"	2	250psi	15 lbs
1/4"	17/32"	2	200psi	21 lbs
5/16"	19/32"	2	200psi	25 lbs
3/8"	21/32"	2	200psi	27 lbs

Green-Oxygen

Red-Acetylene

Single Line Hose - Corrugated Cover

I.D.	O.D.	No. of Spirals	Braid	Working Pressure	Weight per 100'
3/16"	7/16"	2	1	200psi	9 lbs
1/4"	17/32"	2	1	200psi	13 lbs
1/4"	19/32"	4	2	250psi	16 lbs
5/16"	21/32"	4	2	250psi	19 lbs
3/8"	23/32"	4	2	250psi	21 lbs

Grade R For acetylene only, and where cover must resist abrasion, weather and ozone.

Grade RM For acetylene only, and where an oil and flame resistant cover is required.

Grade T For use with all fuel gases, and where an oil and flame resistant cover is required.