


FELTON BRUSHES



# Welders and Pipeline Brushes

## WIRE SCRATCH BRUSHES

Popular all-purpose brush for cleaning structural steel, iron works, castings, all types of dirt and rust removal. Brushes are filled with oil tempered steel wire, stainless steel wire or brass wire.



### CURVED HANDLE

Length of Brush Part 6", 15 cm  
Overall Length 14", 35 cm

Part No.	Model No.	Rows	Block Width		Wire Size	
			in.	mm	in.	mm
601083	FE-1777	3 x 19	15/16	24	.015	.40
601084	FE-1777B	3 x 19	15/16	24	.012	.30
601085	FE-1777SS	3 x 19	15/16	24	.015	.40
601017	FE-188	4 x 19	1 1/8	30	.015	.40
601018	FE-188B	4 x 19	1 1/8	30	.012	.30
601019	FE-188SS	4 x 19	1 1/8	30	.015	.40

B - Brass SS - Stainless Steel



### SHOE HANDLE

Length of Brush Part 5 1/4", 13 cm  
Overall Length 10", 25 cm

Part No.	Model No.	Rows	Block Width		Wire Size		Trim Length	
			in.	mm	in.	mm	in.	mm
601089	FE-1781	4 x 16	1 1/16	27	.015	.40	1 1/8	30
601090	FE-1781B	4 x 16	1 1/16	27	.012	.30	1 1/8	30
601091	FE-1781SS	4 x 16	1 1/16	27	.015	.40	1 1/8	30

B - Brass SS - Stainless Steel



### STRAIGHT BACK - BUTCHER BLOCK STYLE - FLAT STEEL

Part No.	Model No.	Block Size		Rows	Trim Length	
		in.	cm		in.	mm
902041	FE-104	7 5/8 x 2 5/8	19 x 6	5 x 10	1	25
902042	FE-106	7 5/8 x 2 5/8	19 x 6	5 x 10	1 1/2	40

## Specialty Brushes



### DAUBER BRUSH / RIG BRUSH

Long handled brush, designed for hand application of coatings in pipe-laying operations.

Part No.	Model No.	Size		Trim Length	
		in.	cm	in.	cm
9601100	SB1792	20	51	2 7/8	7



### ACID BRUSHES - TIN FERRULE STYLE

Part No.	Model No.	Width		Trim Length		Overall Length	
		in.	mm	in.	mm	in.	mm
902050	SB748	3/8	9	3/4	19	5 3/4	15
902051	SB749	1/2	12	3/4	19	5 3/4	15
902052	SB750	5/8	15	3/4	19	5 3/4	15

## Power Brushes

### CUP BRUSHES - Filled with high quality steel wire.

Felton wire cup brushes are designed for use in high speed pneumatic and electrical portable tools. Brushes are strong, efficient tools for fast heavy-duty cleaning of large metal surfaces. To remove weld scale, rust, old paint and corrosion. For rugged jobs, the knot-type brushes are recommended. Also available with stainless steel.



SINGLE ROW

### TWISTED KNOT WIRE CUP BRUSH - SINGLE ROW

Part No.	Model No.	Diameter		Wire Size		Arbor Hole	MSFS RPM
		in.	mm	in.	mm		
901008	420T	4	100	.035	.90	5/8 threaded	6000
901010	424T	4	100	.020	.50	5/8 threaded	7200
901012	430T	4	100	.014	.35	5/8 threaded	6000



DOUBLE ROW

### TWISTED KNOT WIRE CUP BRUSH - DOUBLE ROW

Part No.	Model No.	Diameter		Wire Size		Arbor Hole	MSFS RPM
		in.	mm	in.	mm		
901001	208T	6	150	.035	.90	5/8 threaded	6000
901003	248T	6	150	.020	.50	5/8 threaded	6000
901006	308T	6	150	.014	.35	5/8	6000

# Speed Whirl Sections



**SPEEDWHIRL SECTIONS** - Filled with high quality steel wire. For high impact brushing, such as removing weld scale, cleaning hard surface incrustations, (particularly when there is extreme adherence), general descaling. Higher speeds than crimped wire brushes, giving greater efficiency and ease of operation. Can be manufactured with a cable twist (wire twisted to end). Also available with stainless steel.

Speedwhirl Section Brushes							
Part No.	Model No.	Diameter		Wire Size		Arbor Hole	MSFS RPM
		in.	mm	in.	mm		
901028	1006	6	150	.023	.58	5/8	9000

# Stringer Bead Brushes



**STRINGER BEAD BRUSHES** - Filled with high quality steel wire. For heavy duty cleaning of weld spatter and slag. Removal of rust, scale and oxidation. Root and hot pass weld cleaning. Stringer bead twist - very narrow face for weld cleaning. Also available with stainless steel.

STRINGER BEAD BRUSHES						
Part No.	Model	Diameter	Face Width	Wire Size	Thread	RPM
901096	814T	4"	1/4"	.020	5/8-11	20,000
901050	815T	5"	1/4"	.020	5/8-11	12,000
901020	816T	6"	1/2"	.023	5/8-11	9,000
901022	817T	6 1/2"	1/4"	.020	5/8-11	12,000

**Other Felton Brushes available in different styles and sizes  
Ask for our complete catalogue !**