

# Safety Data Sheet



According to OSHA 29 CFR 1910.1200 HCS & Canada WHMIS

Revision Date: 26.02.2014

# SECTION 1: Product and Company Identification

1.1. Product identifier

Product Name : Jiffy Artline Paint Marker EK-400 Color : (White)

Artline Paint Marker EK-440
Artline Paint Marker EK-444
Artline Paint Marker EK-409

1.2. Recommended use of the chemical and restrictions on use

Recommended use : Permanent marker ink

1.3. Details of the supplier of the safety data sheet

Supplier Company Name : Jiffco International Ltd.

Address : 835 - West 3rd Street North Vancouver , BC V7P 3K7 Canada

Address : 4-69,Amazuka-cho,Nishi-ku,Nagoya City,451-0021,Japan

Telephone : +81-52-521-3600 Fax : +81-52-521-3899

Contact (e-mail) : <a href="mailto:chem-analysis@ngy.shachihata.co.jp">chem-analysis@ngy.shachihata.co.jp</a>

1.4. Emergency telephone number

Telephone: 604-657-9822

# SECTION 2: Hazard(s) identification

United States (US): According to OSHA 29 CFR 1910.1200 HCS 2012

2.1.1 Classification of the substance or mixture

Flammable liquids, Category 2 H225 : Highly flammable liquid and vapour

Aspiration toxicity, Category 1 H304: May be fatal if swallowed and enters airways

Skin corrosion / irritation , Category 2 H315 : Causes skin irritation

Specific target organ toxicity - single exposure, Category 3 H336 : May cause drowsiness or dizziness

Hazardous to the aquatic environment, H411 : Toxic to aquatic life with long lasting effects

chronic toxicity, Category 2

2.1.2 Label elements

Hazard pictograms :









Signal word : Danger

Hazard statement : Highly flammable liquid and vapour (H225)

May be fatal if swallowed and enters airways

Causes skin irritation

May cause drowsiness or dizziness

Toxic to aquatic life with long lasting effects

(H304)

(H304)

(H304)

(H304)

(H305)

Precautionary statement

[Prevention]

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.(P210)Take precautionary measures against static discharge.(P243)Avoid breathing dust/fume/gas/mist/vapours/spray.(P261)Wear protective gloves/protective clothing/eye protection/face protection.(P280)Wash hands thoroughly after handling.(P264)Use only outdoors or in a well-ventilated area.(P271)

Avoid release to the environment. (P273)

[Response]

In case of fire : Use dry chemical powder,form or carbon dioxide for extinction. (P370+P378)

IF SWALLOWED : Immediately call a POISON CENTER or doctor/physician. (P301+P310)

Get medical advice/attention if you feel unwell. Rinse mouth. (P301+P314+P330)

IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable (P304+P340)

for breathing.

IF IN EYES : Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

(P305+P351+P338)

(P337+P313)

(P331)

(P501)

If eye irritation persists : Get medical advice/attention.

IF ON SKIN (or hair) : Remove/Take off immediately all contaminated clothing. (P303+P361+P353)

Rinse skin with water/shower.

IF ON SKIN : Wash with plenty of soap and water. (P302+P352)

If skin irritation occurs : Get medical advice/attention. (P332+P313)

Do NOT induce vomiting.

Collect spillage. (P391)

[Storage]

Store in a well-ventilated place. Keep container tightly closed. (P403+P233)

[Disposal]

Dispose of contents/container to waste in accordance with

local/regional/ national/international regulation (to be specified).

#### 2.1.3 Other hazards

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada : According to WHMIS

### 2.2.1 Classification of the substance or mixture

Class B2 : Flammable Liquids


2.2.2 Label elements



### 2.2.3 Other hazards

In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS)

## 2.3 Other information





**HMIS** 

# SECTION 3: Composition/information on ingredients

Substance/Mixture : Mixture

Ingredients :

Chemical Name /	Composition	CAS	Classification (OSHA HCS 2012)	
Generic name	weight %	Registry No.	Hazard Class	Hazard statement
Methylcyclohexane	25 ~ 35	108-87-2	Flam.Liq. 2 Asp. Tox. 1 Skin Irrit.2 STOT.SE. 3 Aquatic Chronic 2	H225 H304 H315 H336 H411
Isoparaffinic Hydrocarbon	5 ~ 15	64742-48-9	Flam.Liq. 3 Asp. Tox. 1 Aquatic Chronic 2	H226 H304 H411
Titanium dioxide	30 ~ 40	13463-67-7	none	none
Synthetic resin	15 ~ 25	Confidential	none	none
Additive	1 ~ 10	Confidential	none	none
total	100			

### SECTION 4: First-aid measures

4.1. Description of first aid measures

IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Consult a doctor if symptoms persist.

IF ON SKIN : Remove/Take off immediately all contaminated clothing. Wash with soap and water.

If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.

IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

IF SWALLOWED : After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach,

and do not vomit forcibly. Moreover, do not give anything from the mouth to the patient

when not conscious. Receive the doctor's treatment (stomach pump) promptly.

Note to Physicians:

All treatments should be based on observed signs and symptoms of distress in the patient.

Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

## SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical powder, foam or carbon dioxide

Unsuitable extinguishing media : Water jet

5.2. Special hazards arising from the substance or mixture

For initial stage extinction, carbon dioxide or dry chemical powder.

When a fire extends, fire is extinguished by a large amount of water spray.

Do not discharge extinguishing waters into the aquatic environment.

5.3. Advice for firefighters

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn.

Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

# SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe area. Shut off all sources of ignition.

No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.

6.2. Environmental precautions

Do not throw the leakage thing directly into environment

6.3. Methods and material for containment and cleaning up

In case of a small spill, absorb with dry sand, soil, sawdust, cloth, etc.,

then place in a chemical waste containers.

In case of large spills, dike and prevent overflow, cover spills with foam,

then place in a chemical container using non-sparking tools.

# SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling : Use with adequate ventilation.

Avoid contact with skin, eyes and clothing. Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep containers tightly closed and store in a cool and dry place. areas and containers : Keep away from heat and flame,ignition source and sunlight.

Reep away from fleat and flame, ignition source and sunlight.

Keep out of the reach of children.

# SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ACGIH (2013)

MethylcyclohexaneTWA400ppmTitanium dioxideTWA10 mg/m³

OSHA PEL

MethylcyclohexaneTWA500ppmTitanium dioxideTWA15 mg/m³

Canada Ontario Provincial

Methylcyclohexane TWA 400ppm
Titanium dioxide TWA 10 mg/m³

Canada Quebec Provincial

Methylcyclohexane TWA 400ppm
Titanium dioxide TWA 10 mg/m³

### 8.2. Exposure controls

Personal protective equipment

Respiratory Protection : Use with local exhaust ventilation, when in long use.

Avoid breathing vapours. Wear mask to prevent organic gas, if necessary.

Hand Protection : Avoid contact with hands. Wear safety gloves, if necessary. Eye Protection : Avoid contact with eyes. Wear safety glasses, if necessary.

Skin Protection : Avoid skin contact. Wear personal protection apron, boots, if necessary.

Environmental exposure controls

General advice : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform respective authorities.

# SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : white liquid

Odor : minor solvent odor
pH : Not applicable
Boiling point : No data available

Flash point : 26.6 °F (-3 °C) (closed cup)

Relative Density (at 77 °F, 25 °C) :  $1.2 \sim 1.4$  (g/cm<sup>3</sup>)

Solubility in Water : Insoluble

# SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.3. Chemical stability

The product is stable.

10.4. Conditions to Avoid

High temperature, Direct sunlight, Fire

10.5. Incompatible Materials

No data available

10.6. Hazardous decomposition products

CO, CO<sub>2</sub>

# SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : LD/LC50 values that are relevant for classification

[Methylcyclohexane]

Oral-rat LD50 >5,000mg/kg Inhalation-rat LC50 23.3 mg/l/4H Dermal-rabbit LD50 >2,000mg/kg

[Isoparaffinic Hydrocarbon]

Oral-rat LD50 >5,000mg/kg
Inhalation-rat LC50 >5,000mg/m³
Dermal-rabbit LD50 >5,000mg/kg

Aspiration toxicity, Category 1 : Category 1 May be fatal if swallowed and enters airways.

Skin corrosion / irritation : Category 2 Causes skin irritation.

Specific target organ toxicity

single exposure

: Category 3 May cause drowsiness or dizziness.

Carcinogenicity : Titanium dioxide has been classified by the IARC as Group 2B.

Other materials: Not listed by IARC, ACGIH, OSHA or NTP.

Regarding the carcinogenicity of titanium dioxide, International Agency for Research on Cancer (IARC) has classified as a group 2B. However, ACGIH (American Conference of Governmental Industrial Hygienists), OSHA (Occupational Safety and Health Administration), NTP (National Toxicology Program, USA) in the classification of suspected carcinogenic to humans has not been done. Therefore, we could not classify the carcinogenicity of GHS from that there is no sufficient data.

# SECTION 12: Ecological information

12.1. Ecotoxicity : Category 2 Toxic to aquatic life with long lasting effects

12.2. Persistence and degradability
12.3. Bioaccumulative potential
12.4. Mobility in soil
12.5. No data available
12.6. No data available
12.7. No data available
12.8. No data available
13. No data available
14. No data available
15. No data available
16. No data available

12.5. Other adverse effects : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal must be made according to official regulations.

Comply with all Federal, State, and Local regulations regarding disposal.

Do not allow product to reach ground, any water course or sewage system.

# SECTION 14: Transport information

14.1. UN number DOT, TDG, IMO / IMDG, IATA / ICAO : UN1210

14.2. UN proper shipping name DOT, TDG, IMO / IMDG, IATA / ICAO : PRINTING INK, flammable

14.3. Transport hazard class(es) DOT, TDG, IMO / IMDG, IATA / ICAO :

· Class 3 (Flammable liquids.)

· Label 3

14.4. Packing group DOT, TDG, IMO / IMDG, IATA / ICAO : II
14.5. Environmental hazards Marine pollutant : No

14.6. Special precautions for user EMS Number : F-E,S-D

14.7. Transport in bulk according to Annex II of : Not applicable.

MARPOL 73/78 and the IBC Code

# SECTION 15: Regulatory information

#### < USA Information >

OSHA STATUS : This product is hazardous under 29 CFR 1910.1200.

TSCA inventory : All components of this product are listed in the TSCA Inventory.

TSCA Hazard Communication Program (40 CFR Part 721) (SNUR) : not Listed EPCRA Section 302 Extremely Hazardous Substances (EHS) : not Listed EPCRA Section 313 Toxic Chemicals : not Listed CERCLA Hazardous Substances : not Listed CAA Section 112(r) List of Substances for Accidental Release Prevention : not Listed California Proposition 65 : not Listed

### < Canada Information >

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

Canada inventory : All components of this product are listed in the DSL/NDSL Inventory.

WHMIS Ingredient Disclosure List (SOR/88-64) : Methylcyclohexane

(WHMIS: Canadian Workplace Hazardous Material Information System)



# SECTION 16: Other information, including date of preparation or last revision

Last Revision Date : 26.02.2014 Preparation Date : 02.04.2007



EU RoHS Directive(2002/95/EC) and ELV Directive(2000/53/EC) This product does not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenylethers (PBDE).

This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.