



## Safety Data Sheet

Dynaflux SDS 200B 07/18/2018

Product: 200 Heavy Duty Anti-Spatter (Liquid)

**Part 1: Product and Company Identification**

Identification 200B

Trade Name: 200 Heavy Duty Anti-Spatter

Product Use: Heavy Duty Ant-Spatter.

Manufacturers Name: Dynaflux, Inc.

241 Brown Farm Rd.

Cartersville, GA 30120 U.S.A.

Preparation Date: 08/13/2013

Emergency Telephone Number: For U.S.: 800-255-3924 International: 813-248-0585

**Part 2: Hazard(s) Identification**

Signal Word:

Danger

Hazard Statements

Causes skin irritation

Causes serious eye irritation

May cause drowsiness or dizziness

May cause cancer

**Part 3: Composition / Information on ingredients**

Hazardous Ingredients	CAS No.	SARA III List	PEL PPM	TLV PPM	Carcinogen Refer. Source
Dichloromethane	75-09-2	Yes	25	12.5	IARC NTP

**Potential Acute Health Effects:** Very hazardous in case of eye contact (irritant), of ingestion, of inhalation. Hazardous in case of skin contact (irritant, permeator). Inflammation of the eye is characterized by redness, watering and itching.

**Part 4: First Aid Measures****Eye Contact:**

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention immediately. **GHS Subcategory 2A**

**Skin Contact:**

In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention. **GHS Category 3**

**Inhalation:**

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, Get medical attention.

**Ingestion:**

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband. **GHS Category 4**

**Reproductive Toxicity: GHS Category 2**

**Carcinogenicity: GHS Category 2**

**Part 5: Fire Fighting Measures**

**Auto-Ignition Temperature:** 556°C (1032.8°F).

**Flash Points:** Non-flammable.

**Flammable Limits:** LOWER: 12% UPPER 19%

**Products of Combustion:** These products are carbon oxides (CO, CO<sub>2</sub>), halogenated compounds and small amounts of phosgene.

**Fire Hazards in Presence of Various Substances:** Not available.

**Fire Fighting Media and Instructions:** SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet. Cool containers to help prevent rupturing.

**Part 6: Accidental Release Measures****Small Spill:**

Mop up or absorb with an inert dry material and place in an appropriate waste disposal container.

**Large Spill:**

Dike area and pump to an intact, labeled container. Mop up or absorb on an inert material. Sweep up and place in a labeled container.

**Part 7: Handling and Storage**

Keep away from heat. Do not ingest. Do not breathe gas/fumes/vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

**Storage:** Keep container tightly closed. Keep container in a cool, well-ventilated area.

**Part 8: Exposure Control / Personal Protection****Engineering Controls:**

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work station location.

**Personal Protection:**

Splash goggles. Apron. Vapor respirator. Be sure to use an approved/certified respirator. Gloves

**Personal Protection in Case of a Large Spill:**

Splash goggles, full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product.

**Exposure Limits:**

TWA: 50 from ACGIH (TLV) [United States] TWA: 174 from ACGIH (TLV) [United States] Consult local authorities for acceptable exposure limits.

Continued

## Part 9: Physical and Chemical Properties

**Physical state and appearance:** Light amber liquid.

**Odor:** Mild, sweet

**Molecular Weight:** 84.94

**Specific Gravity:** (water =1.0): 1.33

**Solubility in Water (weight %):** 1.32 gm/100gm @ 77°F (25°C)

**pH:** Not applicable

**Boiling Point:** 104°F (40°C).

**Vapor Pressure:** 350mm Hg at 68°F (20°C).

**Vapor Density (Air=1):** 2.9

**Evaporation Rate:** 0.7 Compared to: Ethyl Ether = 1

**% Volatiles:** 100

**Flash Point:** None

## Part 10: Stability and Reactivity

### Stability:

Stable under recommended storage conditions.

Avoid: Incompatible products

### Incompatibilities:

Open flames, amines and strong bases.

### Hazardous Polymerization:

Hazardous polymerization does not occur.

## Part 11: Toxicological Information

Component Analysis – LD50/LC50

### Dichloromethane (75-09-2)

Ingestion: Rat: LD50 1500-2500 mg/kg

Inhalation: Rat LC50 10,000 ppm

Carcinogenicity Classification: N.T.P. Anticipated Carcinogen. IARC: Possible carcinogen; 2B

Reproductive Toxicity: animal studies-None

## Part 12: Ecological Information

Potential for mobility in soil is high.

Octanol/Water partition coefficient: 1.25

Organic carbon/water partition coefficient: 24

Atmospheric half life: 79-110 days

Biodegradation 5-26% 28 days

LC50 bluegill: 224 mg/l

Aquatic Toxicity EC50 water flea. Immobilization: 480 mg/l

## Part 13: Disposal Consideration

Waste Information: Dispose of as special waste in compliance with local and national regulations. Waste codes should be assigned by the user based on the application for which the product was used. Incineration of waste material in an EPA-approved facility is recommended, allowing a solid, inert residue to form.

**Other Disposal Considerations:** Observe all Federal, State and Local Environmental regulations.

## Part 14: Transportation Information

**DOT Hazard Classification:** Dichloromethane Solution, UN1953, 6.1, PG III, RQ 1000lb / 454kg

## Part 15: Regulatory Information

**TSCA** – The product on this MSDS, or all of its components, is listed under TSCA.

**Section 311 Hazard Class:** 6.1.

**SARA 313 Toxic Chemicals:**

The following ingredients are SARA 313 “Toxic Chemicals”.

**Ingredient Name:**

Dichloromethane (75-09-2)

**WHMIS Classification (Canada):**

CLASS D-1B: Material causing immediate and serious toxic effects (TOXIC). CLASS D-2A: Material causing other toxic effects.

**DSCL (EEC):** R22-harmful if swallowed. R38- irritating to skin. R41- Risk of serious damage to eyes. R45- may cause cancer.

**California Proposition 65 Statement:**



**WARNING:** This product can expose you to Dichloromethane, a chemical known to the State of California to cause cancer. For more information, go to [www.p65Warnings.ca.gov/product](http://www.p65Warnings.ca.gov/product).

## Part 16: Other Information

Dynaflux, Inc.

241 Brown Farm Rd.

Cartersville, GA 30120 U.S.A.

**Disclaimer of Expressed and implied Warranties:**

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date of the Safety Data sheet was prepared. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices as specified on the label copy.