SAFETY DATA SHEET

1. Identification

Product identifier NOZZLE-KLEEN® Anti-Spatter

Other means of identification

No. YOR-107-A (Item# 1008304) **Product Code**

Recommended use Protects nozzles, diffusers, and tips from spatter build-up

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries. Inc. Company name

885 Louis Dr. **Address**

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical Assistance** 800-521-3168 **Customer Service** 800-272-4620 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable aerosols

Gases under pressure

Not classified. **Health hazards Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Precautionary statement

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open Prevention

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh

Category 1

Liquefied gas

air supply during use and while product is drying.

Response Wash hands after handling.

Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding Storage

50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
white mineral oil		8042-47-5	40 - 50
n-butane		106-97-8	20 - 40
propane		74-98-6	20 - 40
oleic acid		112-80-1	1 - 10

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Rinse with water. Get medical attention if irritation develops and persists.

Eye contact Rinse with plenty of water. Get medical attention if irritation develops and persists.

Ingestion In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. Do

not induce vomiting without advice from poison control center. If vomiting occurs, keep head low

so that stomach content doesn't get into the lungs.

Direct contact with eyes may cause temporary irritation.

Most important

treatment needed

symptoms/effects, acute and delayed

Indication of immediate medical attention and special

Provide general supportive measures and treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

During fire, gases hazardous to health may be formed.

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Water fog. Foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without

risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire

and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when

exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

SDS US

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
white mineral oil (CAS 8042-47-5)	PEL	5 mg/m3	Mist.
US. ACGIH Threshold Limit Value	es		
Components	Type	Value	Form
n-butane (CAS 106-97-8)	STEL	1000 ppm	
white mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Type	Value	Form
n-butane (CAS 106-97-8)	TWA	1900 mg/m3	
,	1 1 1 1 1		
	1000	•	
propane (CAS 74-98-6)	TWA	800 ppm 1800 mg/m3	
propane (CAS 74-98-6)		800 ppm	
propane (CAS 74-98-6) white mineral oil (CAS 8042-47-5)		800 ppm 1800 mg/m3	Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Neoprene.

Other Wear suitable protective clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Liquid. Physical state Aerosol. **Form**

Colorless to amber. Color

Odor Mild.

Not available. **Odor threshold** Not available.

61.3 °F (16.3 °C) estimated Melting point/freezing point

Initial boiling point and boiling

range

< 600 °F (< 315.6 °C)

259.5 °F (126.4 °C) Flash point **Evaporation rate** Not available.

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

1.9 % estimated

(%)

Flammability limit - upper

(%)

9.5 % estimated

3247.3 hPa estimated Vapor pressure > 1 (air = 1)

Vapor density 0.87

Relative density

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 650 °F (343.3 °C) estimated

Decomposition temperature Not available. Not available. **Viscosity** 95 % estimated Percent volatile

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials Strong oxidizing agents. Chlorine. Fluorine. Nitrates.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Material name: NOZZLE-KLEEN® Anti-Spatter

No. YOR-107-A (Item# 1008304) Version #: 01 Issue date: 06-05-2018

Symptoms related to the physical, chemical and

Information on toxicological effects

toxicological characteristics

Acute toxicity Not known.

Components Species Test Results

propane (CAS 74-98-6)

Acute Dermal

LD50 Rabbit > 5000 mg/kg

white mineral oil (CAS 8042-47-5)

<u>Acute</u>

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 5 mg/l, 4 hours

Skin corrosion/irritation Serious eye damage/eye Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

white mineral oil (CAS 8042-47-5)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not likely, due to the form of the product.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

oleic acid (CAS 112-80-1)

Aquatic Acute

Fish LC50 Rainbow trout, donaldson trout 56 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

n-butane 2.89 propane 2.36

Mobility in soil No data available.

Material name: NOZZLE-KLEEN® Anti-Spatter

The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Not regulated. Hazardous waste code

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). **Disposal instructions**

Empty container can be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose in

accordance with all applicable regulations.

14. Transport information

DOT

UN1950 **UN** number

UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82 306 Packaging exceptions Packaging non bulk 304 Packaging bulk None

IATA

UN1950 **UN** number

UN proper shipping name Aerosols, flammable, Limited Quantity

Transport hazard class(es)

2.1 Class Subsidiary risk

Not applicable. Packing group

ERG Code 101

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

AEROSOLS, Limited Quantity

IMDG

UN number UN1950

UN proper shipping name Transport hazard class(es)

2 Class Subsidiary risk

Packing group Not applicable.

Environmental hazards

No. Marine pollutant F-D, S-U **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

No. YOR-107-A (Item# 1008304) Version #: 01 Issue date: 06-05-2018

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

n-butane (CAS 106-97-8) propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Flammable (gases, aerosols, liquids, or solids) **Classified hazard**

categories Gas under pressure

Acute toxicity (any route of exposure)

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

n-butane (CAS 106-97-8) propane (CAS 74-98-6)

US. Massachusetts RTK - Substance List

n-butane (CAS 106-97-8) propane (CAS 74-98-6) white mineral oil (CAS 8042-47-5)

US. Pennsylvania Worker and Community Right-to-Know Law

n-butane (CAS 106-97-8) oleic acid (CAS 112-80-1) propane (CAS 74-98-6) white mineral oil (CAS 8042-47-5)

US. Rhode Island RTK

n-butane (CAS 106-97-8) oleic acid (CAS 112-80-1) propane (CAS 74-98-6) white mineral oil (CAS 8042-47-5)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65); This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

n-butane (CAS 106-97-8)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR < 60 % 51.100(s))

Consumer products (40 CFR 59, Subpt. C)

oducts Not regulated

State

Taiwan

Consumer products Not regulated

VOC content (CA) < 60 % VOC content (OTC) < 60 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Taiwan Toxic Chemical Substances (TCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date06-05-2018Prepared byAllison Yoon

Version # 01

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Material name: NOZZLE-KLEEN® Anti-Spatter

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).