

SAFETY DATA SHEET

(in accordance with The Hazard Communication Standard (HCS) (29 CFR 1910.1200))

1826S002047-WS CRACK 5 S 10,20 oz



Version: 1
Revision date: 2/24/2023

Page 1 of 12
Print date: 2/24/2023

Section 1: Identification.

Product identifier used on the label and Other means of identification.

Product Name: WS CRACK 5 S 10,20 oz
Product Code: 1826S002047

Recommended use of the chemical and restrictions on use.

Ensayo NDT

Specific end use(s).

Reservado a un uso profesional

Uses advised against:

Uses other than those recommended.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party.

Company: **WHALE SPRAY S.L.**
Address: Carrer Aiguafreda 24, Nave 1-2, P.I.L'Ametlla Park 08480 -
City: L'Ametlla del Vallés
Province: Barcelona
Telephone: +1 (615) 616-8934 (USA 24 hours emergency number)
E-mail: whalespray@whalespray.com
Web: <https://whalespray.com/>

Emergency phone number: +1 (615) 616-8934

Section 2: Hazard(s) Identification.

Classification of the chemical in accordance with paragraph (d) of §1910.1200

In accordance with The Hazard Communication Standard (HCS) (29 CFR 1910.1200):

Flammable aerosol, Category 1 : Extremely flammable aerosol.

Eye irritation, Category 2A : Causes serious eye irritation.

Specific target organ toxicity following a single exposure, Category 3 : May cause drowsiness or dizziness.

Signal word, hazard statement(s), symbol(s) and precautionary statement(s) in accordance with paragraph (f) of §1910.1200.

Symbol(s):



Signal Word:

Danger

Hazard statement(s):

H222 Extremely flammable aerosol.
H229 Pressurized container: may burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statement(s):

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with The Hazard Communication Standard (HCS) (29 CFR 1910.1200))

1826S002047-WS CRACK 5 S 10,20 oz



Version: 1
Revision date: 2/24/2023

Page 2 of 12
Print date: 2/24/2023

Section 3: Composition/Information on Ingredients.

Substances.

Not Applicable.

Mixtures.

Chemical name and concentration ranges of all ingredients that are classified as health hazards in accordance with paragraph (d) of §1910.1200 and that are present above their cut-off/concentration limits or ingredients that are below their cut-off/concentration limits and present a health risk:

Identifiers	Name	Concentrate	(*)Classification	
			Classification	specific concentration limit
Index No: 606-001-00-8 CAS No: 67-64-1 EC No: 200-662-2 REACH No: 01-2119471330-49-XXXX	[1] acetone,propan-2-one,propanone	20 - 75 %	Eye Irrit. 2A, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
Index No: 603-117-00-0 CAS No: 67-63-0 EC No: 200-661-7 REACH No: 01-2119457558-25-XXXX	[1] isopropanol,isopropyl alcohol,propan-2-ol	10 - 20 %	Eye Irrit. 2A, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-

(*)The complete text of the Hazard statement(s) is given in section 16 of this Safety Data Sheet.

[1] Substance with a workplace exposure limit (see section 8.1).

Section 4: First-Aid Measures.

Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

Section 5: Fire-Fighting Measures.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with The Hazard Communication Standard (HCS) (29 CFR 1910.1200))

1826S002047-WS CRACK 5 S 10,20 oz



Version: 1
Revision date: 2/24/2023

Page 3 of 12
Print date: 2/24/2023

In case of fire, as a general hazard, heat can cause containers to explode. The product is Extremely flammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.
- Explosions.

Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available. Move containers away from the area if there is no danger in doing so. Keep away from containers and continue cooling them from a safe place.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

Section 6: Accidental Release Measures.

Personal precautions, protective equipment, and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. Isolate the area and ensure adequate ventilation. Stockpiling in basements, pits or any confined space or depressed area can be hazardous. For exposure control and individual protection measures, see section 8.

Environmental precautions: Product not classified as hazardous for the environment, avoid spillage as much as possible.

Methods and materials for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

Reference to other sections: for exposure control and individual protection measures, see section 8, for later elimination of waste, follow the recommendations under section 13.

Section 7: Handling and Storage.

Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with The Hazard Communication Standard (HCS) (29 CFR 1910.1200))

1826S002047-WS CRACK 5 S 10,20 oz



Version: 1
Revision date: 2/24/2023

Page 4 of 12
Print date: 2/24/2023

Follow legislation on occupational health and safety.

Pressurised gases must be handled by suitably trained and experienced individuals. Use equipment suitable for supply pressure and temperature. Protect containers against physical damage and keep valves clean and in perfect condition. Do not tamper with original packaging.

Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. It must not be stored under conditions conducive to corrosion of the container. Protect containers against physical damage and inspect them regularly to ensure they are in good condition.

Section 8: Exposure Controls/Personal Protection.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
acetone,propan-2-one,propanone	67-64-1	United States [1] (Cal/OSHA)	Eight hours	500	
			Short term	750 (Ceiling) 3000	
		United States [2] (NIOSH)	Eight hours	250	
			Short term		
		United States [3] (OSHA)	Eight hours	1000	2400
			Short term		
isopropanol,isopropyl alcohol,propan-2-ol	67-63-0	United States [1] (Cal/OSHA)	Eight hours	400	
			Short term	500	
		United States [2] (NIOSH)	Eight hours	400	
			Short term	500	
		United States [3] (OSHA)	Eight hours	400	980
			Short term		

[1] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[2] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[3] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
acetone,propan-2-one,propanone CAS No: 67-64-1 EC No: 200-662-2	DNEL (Workers)	Inhalation, Chronic, Systemic effects	1210 (mg/m ³)
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	200 (mg/m ³)
	DNEL (Workers)	Inhalation, Short term, Local effects	2420 (mg/m ³)
	DNEL (Workers)	Dermal, Chronic, Systemic effects	186 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	62 (mg/kg bw/day)
	DNEL (Consumers)	Oral, Chronic, Systemic effects	62 (mg/kg bw/day)
isopropanol,isopropyl alcohol,propan-2-ol CAS No: 67-63-0 EC No: 200-661-7	DNEL (Workers)	Inhalation, Chronic, Systemic effects	500 (mg/m ³)
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	89 (mg/m ³)
	DNEL (Workers)	Dermal, Chronic, Systemic effects	888 (mg/kg bw/day)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with The Hazard Communication Standard (HCS) (29 CFR 1910.1200))

1826S002047-WS CRACK 5 S 10,20 oz



Version: 1
Revision date: 2/24/2023

Page 5 of 12
Print date: 2/24/2023

	DNEL (Consumers)	Dermal, Chronic, Systemic effects	319 (mg/kg bw/day)
	DNEL (Consumers)	Oral, Chronic, Systemic effects	26 (mg/kg bw/day)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
acetone,propan-2-one,propanone CAS No: 67-64-1 EC No: 200-662-2	aqua (freshwater)	10,6 (mg/L)
	aqua (marine water)	1,06 (mg/L)
	aqua (intermittent releases)	21 (mg/L)
	STP	100 (mg/L)
	sediment (freshwater)	30,04 (mg/kg sediment dw)
	sediment (marine water)	3,04 (mg/kg sediment dw)
	soil	29,5 (mg/kg soil dw)
isopropanol,isopropyl alcohol,propan-2-ol CAS No: 67-63-0 EC No: 200-661-7	aqua (freshwater)	140,9 (mg/L)
	aqua (marine water)	140,9 (mg/L)
	aqua (intermittent releases)	140,9 (mg/L)
	sediment (freshwater)	552 (mg/kg sediment dw)
	sediment (marine water)	552 (mg/kg sediment dw)
	Soil	28 (mg/kg soil dw)
	STP	2251 (mg/L)
	oral (Hazard for predators)	160 (mg/kg food)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Ensayo NDT
Breathing protection:	
If the recommended technical measures are observed, no individual protection equipment is necessary.	
Hand protection:	
PPE:	Work gloves.
Characteristics:	«CE» marking, category I. Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible.
Maintenance:	Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.
Material:	PVC (polyvinyl chloride)
Breakthrough time (min.):	> 480
Material thickness (mm):	0,35
Eye protection:	
If the product is handled correctly, no individual protection equipment is necessary.	
Skin protection:	
If the product is handled correctly, no individual protection equipment is necessary.	

Section 9: Physical and Chemical Properties.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with The Hazard Communication Standard (HCS) (29 CFR 1910.1200))

1826S002047-WS CRACK 5 S 10,20 oz



Version: 1
Revision date: 2/24/2023

Page 6 of 12
Print date: 2/24/2023

Information on basic physical and chemical properties.

Appearance: Aerosol

Colour: White

Odour: Not applicable/Not available due to the nature/properties of the product

Odour threshold: Not applicable/Not available due to the nature/properties of the product

pH: Not applicable (Substance/mixture is a gas).

Melting point/freezing point: Not applicable/Not available due to the nature/properties of the product

Initial boiling point or boiling range: Not applicable/Not available due to the nature/properties of the product

Flash point: -16 °C

Evaporation rate: Not applicable/Not available due to the nature/properties of the product

Flammability (solid, gas): Not applicable/Not available due to the nature/properties of the product

Lower Explosive Limit: Not applicable/Not available due to the nature/properties of the product

Upper Explosive Limit: Not applicable/Not available due to the nature/properties of the product

Vapour pressure: Not applicable/Not available due to the nature/properties of the product

Vapour density: Not applicable/Not available due to the nature/properties of the product

Relative density: Not applicable/Not available due to the nature/properties of the product

Solubility: Not applicable/Not available due to the nature/properties of the product

Liposolubility: Not applicable/Not available due to the nature/properties of the product

Hydrosolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient (n-octanol/water): Not applicable/Not available due to the nature/properties of the product

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product

Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

Viscosity: Not applicable/Not available due to the nature/properties of the product

Other information.

Explosive properties: Not applicable/Not available due to the nature/properties of the product

Oxidizing properties: Not applicable/Not available due to the nature/properties of the product

Pour point: Not applicable/Not available due to the nature/properties of the product

Blink: Not applicable/Not available due to the nature/properties of the product

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

Section 10: Stability and Reactivity.

Reactivity.

If the storage conditions are satisfied, does not produce dangerous reactions.

Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

Possibility of hazardous reactions.

Extremely flammable aerosol.

At high temperatures can occur pyrolysis and dehydrogenation.

Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Static discharge.
- Contact with incompatible materials.
- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.
- Explosives materials.
- Toxic materials.
- Oxidizing materials.

Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with The Hazard Communication Standard (HCS) (29 CFR 1910.1200))

1826S002047-WS CRACK 5 S 10,20 oz



Version: 1
Revision date: 2/24/2023

Page 7 of 12
Print date: 2/24/2023

Section 11: Toxicological Information.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
acetone,propan-2-one,propanone CAS No: 67-64-1 EC No: 200-662-2	Oral	LD50	Rat	5800 mg/kg bw [1] [1] Journal of Toxicology and Environmental Health. Vol. 15, Pg. 609, 1985
	Dermal			
	Inhalation			
isopropanol,isopropyl alcohol,propan-2-ol CAS No: 67-63-0 EC No: 200-661-7	Oral	LD50	Rat	5050 mg/kg bw [1] [1] Gigena i Sanitariya. For English translation, see HYSAAV. Vol. 43(1), Pg. 8, 1978
	Dermal	LD50	Rabbit	12800 mg/kg bw [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 100, 1974
	Inhalation	LC50	Rat	>10000 ppm (6 h) [1] [1] OECD Guideline 403 (Acute Inhalation Toxicity), study report, 1991

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Not conclusive data for classification.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3: May cause drowsiness or dizziness.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with The Hazard Communication Standard (HCS) (29 CFR 1910.1200))

1826S002047-WS CRACK 5 S 10,20 oz



Version: 1
Revision date: 2/24/2023

Page 8 of 12
Print date: 2/24/2023

Substances present in the composition listed in the National Toxicology Program (NTP) Report on Carcinogens (RoC):

This product does not contain substances listed in the National Toxicology Program (NTP) Report on Carcinogens (RoC).

Substances present in the composition listed in the International Agency for Research on Cancer (IARC) Monographs:

CAS No.	Agent	*Group	Volume	Year	Additional information
67-63-0	isopropanol,isopropyl alcohol,propan-2-ol	3	15, Sup 7, 71	1999	

* GROUP
Group 3 Not classifiable as to its carcinogenicity to humans

Section 12: Ecological Information.

Ecotoxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
acetone,propan-2-one,propanone CAS No: 67-64-1 EC No: 200-662-2	Fish	LC50	Fish	8300 mg/l (96 h) [1] [1] Cairns, J.Jr., and A. Scheier 1968. A Comparison of the Toxicity of Some Common Industrial Waste Components Tested Individually and Combined. Prog.Fish-Cult. 30(1):3-8
	Aquatic invertebrates	LC50	Crustacean	8450 mg/l (48 h) [1] [1] Cowgill, U.M., and D.P. Milazzo 1991. The Sensitivity of Ceriodaphnia dubia and Daphnia magna to Seven Chemicals Utilizing the Three-Brood Test. Arch.Environ.Contam.Toxicol. 20(2):211-217. Canton, J.H., and D.M.M. Adema 1978. Reproducibility of Short-Term and Reproduction Toxicity Experiments with Daphnia magna and Comparison of the Sensitivity of Daphnia magna with Daphnia pulex and Daphnia cucullata in Short-Term Experiments. Hydrobiologia 59(2):135-140 (Used Reference 2018)
	Aquatic plants	EC50	Algae	7200 mg/l (96 h) [1] [1] Slooff, W. 1982. A Comparative Study on the Short-Term Effects of 15 Chemicals on Fresh Water Organisms of Different Tropic Levels. Natl.Tech.Inf.Serv., Springfield, VA :25 p. (DUT) (ENG ABS) (NTIS/PB83-200386)
isopropanol,isopropyl alcohol,propan-2-ol CAS No: 67-63-0 EC No: 200-661-7	Fish	LC50	Fish	9640 mg/l (96 h) [1] [1] Brooke, L.T., D.J. Call, D.L. Geiger, and C.E. Northcott 1984. Acute Toxicities of Organic Chemicals to Fathead Minnows (Pimephales promelas), Vol. 1. Center for Lake Superior Environmental Stud., Univ.of Wisconsin-Superior, Superior, WI :414
	Aquatic invertebrates	LC50	Crustacean	1400 mg/l (48 h) [1] [1] Blackman, R.A.A. 1974. Toxicity of Oil-Sinking Agents. Mar.Pollut.Bull. 5:116-118
	Aquatic plants	Toxicity threshold	Scenedesmus quadricauda	1800 mg/L (7 d) [1] [1] Comparison of the Toxicity Thresholds of Water Pollutants to Bacteria, Algae, and Protozoa in the Cell Multiplication Inhibition Test, Water Research Vol. 14. pp. 231 to 241

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with The Hazard Communication Standard (HCS) (29 CFR 1910.1200))

1826S002047-WS CRACK 5 S 10,20 oz

Version: 1

Revision date: 2/24/2023



Page 9 of 12

Print date: 2/24/2023

Persistence and degradability.

No information is available regarding the biodegradability of the substances present.
No information is available on the degradability of the substances present.
No information is available about persistence and degradability of the product.

Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
acetone,propan-2-one,propanone CAS No: 67-64-1 EC No: 200-662-2	-0,24	3	-	Very low
isopropanol,isopropyl alcohol,propan-2-ol CAS No: 67-63-0 EC No: 200-661-7	0,05	-	-	Very low

Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

Other adverse effects.

No information is available about other adverse effects for the environment.

Section 13: Disposal Considerations.

Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of the Resource Conservation and Recovery Act (RCRA) and the Resource Conservation and Recovery Act Information (RCRAInfo) regarding waste management.

Section 14: Transport Information.

Transport following the rules of U.S. Department of transportation Pipeline and Hazardous Materials Safety Administration.

In accordance with DOT

Transport document description: UN1950 Aerosols, flammable, (each not exceeding 1 L capacity), 2.1

UN-No.(DOT): UN1950

Proper Shipping Name (DOT): Aerosols, flammable, (each not exceeding 1 L capacity)

Class (DOT): 2.1 - Flammable gas

Hazard labels (DOT): 2.1 - Flammable gas

Packing group:

Special Provisions (172.102): N82

Packaging authorizations:

- a) Exceptions: 306
- b) Non-bulk: None

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with The Hazard Communication Standard (HCS) (29 CFR 1910.1200))

1826S002047-WS CRACK 5 S 10,20 oz

Version: 1

Revision date: 2/24/2023



Page 10 of 12
Print date: 2/24/2023

c) Bulk: None

Quantity Limitations:

- a) Passenger, Aircraft, or Railcar: 75 kg
- b) Cargo Aircraft Only: 150 kg

Vessel Stowage Requirements:

- a) Vessel Stowage: A
- b) Other: 25, 87, 126

Regulations Concerning the International Carriage of Dangerous Goods by Road (ADR)

UN number.

UN No: UN1950

UN proper shipping name.

Description:

ADR/RID: UN 1950, AEROSOLS, 2.1

IMDG: UN 1950, AEROSOLS, 2.1

ICAO/IATA: UN 1950, AEROSOLS, 2.1

Transport hazard class(es).

Class(es): 2

Packing group.

Packing group: Not applicable.

Environmental hazards.

Marine pollutant: No

Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

Special precautions for user.

Labels: 2.1



Hazard number: Not applicable.

ADR LQ: 1 L

IMDG LQ: 1 L

ICAO LQ: Not applicable.

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-D,S-U

Proceed in accordance with point 6.

Section 15: Regulatory Information.

Safety, health and environmental regulations specific for the product.

VVOC: Very volatile organic compounds.

VOC: Volatile organic compounds.

SVOC: Semi volatile organic compounds.

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
67-64-1	acetone,propan-2-one,propanone	

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with The Hazard Communication Standard (HCS) (29 CFR 1910.1200))

1826S002047-WS CRACK 5 S 10,20 oz



Version: 1
Revision date: 2/24/2023

Page 11 of 12
Print date: 2/24/2023

67-63-0	isopropanol,isopropyl alcohol,propan-2-ol	
---------	-------------------------------------------	--

The product is not affected by the procedure established by the Rotterdam Convention, concerning the export and import of dangerous chemicals.

The Superfund Amendments and Reauthorization Act (SARA).

SARA Title III and it sets requirements for local and state emergency planning around hazardous chemicals, the right of the public to access information on chemical hazards in their community, and the reporting responsibilities for facilities that use, store, and / or release hazardous chemicals.

SARA Title III has four provisions (any facility with responsibilities under one section will likely have additional responsibilities under another section, consult SARA for more information):

- Emergency Planning (Sections 301-303)
- Emergency Release Notification (Section 304)
- Hazardous Chemical Storage Reporting Requirements (Section 311-312)
- Toxic Chemical Release Inventory (Section 313)

Information related to the product:

Section 302, Extremely Hazardous Substances (EHSs)(40 CFR part 355 Appendix A and Appendix B) and section 304, in the event of an accidental chemical release that exceeds minimal Reportable Quantity (RQ):

Not Applicable.

Section 311, Requires facilities with hazardous chemicals in quantities above certain thresholds (consult OSHA for more information) to provide copies of the SDSs for those chemicals to the State Emergency Response Commission (SERC), Local Emergency Planning Committee (LEPC) and local fire department.

Section 312, Companies with chemicals in sufficient quantities to trigger obligations under Section 311 must also submit an annual emergency and hazardous chemical inventory form to the State Emergency Response Commission (SERC), Local Emergency Planning Committee (LEPC) and local fire department

Section 313, requires facilities with 10 or more employees that use certain toxic chemicals in quantities above threshold levels to report annually on the use, release and disposal of those chemicals, substances identified in section 3:

Not Applicable.

Visit the EPA's website for the most up-to-date information on EPCRA and other environmental considerations.

Proposition 65 warnings

Information related to The Safe Drinking Water and Toxic Enforcement Act of 1986, (better known by its original name of Proposition 65):

There are no substances in section 3 present in the list of chemicals that can cause cancer, birth defects or other reproductive harm (Proposition 65 List).

Section 16: Other Information.

Complete text of the hazard statement(s) that appear in section 3:

- H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Classification codes:

- Aerosol 1 : Flammable aerosol, Category 1
Eye Irrit. 2A : Eye irritation, Category 2A
Eye Irrit. 2A : Eye irritation, Category 2A
Flam. Liq. 2 : Flammable liquid, Category 2
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with The Hazard Communication Standard (HCS) (29 CFR 1910.1200))

1826S002047-WS CRACK 5 S 10,20 oz



Version: 1
Revision date: 2/24/2023


Page 12 of 12
Print date: 2/24/2023

Classification and procedure used to derive the classification for mixtures according to The Hazard Communication Standard (HCS) (29 CFR 1910.1200):

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Risk classification system NFPA 704:



Abbreviations and acronyms used:

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.

BCF: Bioconcentration factor.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

EC50: Half maximal effective concentration.

PPE: Personal protection equipment.

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

NOEC: No observed effect concentration.

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

The Hazard Communication Standard (HCS) (29 CFR 1910.1200)

United Nations Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

<https://www.osha.gov>

<https://www.epa.gov/>

<http://echa.europa.eu/>

The information given in this Safety Data Sheet has been drafted in accordance with The Hazard Communication Standard (HCS) (29 CFR 1910.1200) and United Nations Globally Harmonized System of Classification and Labelling of Chemicals (GHS). Employers must ensure that the SDSs are readily accessible to employees for all hazardous chemicals in their workplace.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

-End of safety data sheet.-